| | 이 가지 않는 것을 통하는 것이 없는 것이다. | | | |
|-------|---------------------------|-----------------------|-------|----|
| | NAME | | VOLTS | |
| 588 - | COMPACT | | 12 | 24 |
| 900 - | . : | DESCRIPTION | | |
| | BYCOOL GREEN LINE | AIR CONDITIONING UNIT | | |
| | | | | |

No-idle A/C System. Comfort and safety on the road.

Compact is a range of no-idle air conditioning units specially designed for on-road vehicles. Rooftop-mounted and directly powered from the vehicle battery, these units are the ideal solution for the driver's rest at night.







dirna 🏶 Bergstrom.

You'll be comfortable with all these advantages:

- **Driver comfort** supplies a comfortable cab temperature providing maximum comfort without idling the truck engine.
- Fuel savings keeps the cab cool without the truck engine idling, which translates to important savings and quick investment amortisation.
- Ensure road safety facilitates a refreshing rest on the vehicle and alleviates tiredness, which is one of the major causes of road accidents.

Installation



- Available in 24V or 12V (Compact 1.4).
- Easy mounting (without drilling the cab roof on trucks with a a hatch).
- Digital thermometer in °C & °F.

5 ventilation speeds.

• Low maintenance.

- Remote control by radio frequency (RF).
- Pre-charged systems with R134A.
- Double battery protection.
- Two compressors with two independent circuits.



Technical specifications

| MODEL | COMPACT 1.4 | COMPACT 3.0 | |
|------------------------|------------------------|-----------------------------|--|
| Voltage | 12V / 24V | 24V | |
| Power W (*) | 1.400 W | 3.000 W máx. | |
| BTU (*) | 4.777 BTU/h | 10.236 BTU/h máx. | |
| Electrical Consumption | 12V = 18-28 A/h (**) | Engine OFF = 11-24 A/h (**) | |
| | 24V = 10,5-18 A/h (**) | Engine ON = 25-38 A/h (**) | |
| Maximum air flow | 800m ³ | 800m ³ | |
| Use | Night | Night & Day | |
| Dimensions | 826 x 726 x 179 mm | 826 x 726 x 205 mm | |
| Weight | 29,9 kg | 39,3 kg | |

(*) In accordance with JIS standard, test conditions: outside temperature 35°C, return temperature 27 °C (**) Test conditions: outside temperature between 30°C and 42 °C.

Warranty

• 2 years (following our general sales conditions available at www.dirna.com)

DIRNA BERGSTROM, S.L. Francisco Alonso 6. E-28806 Alcalá de Henares (Madrid). Spain España: Tel. +34 91 877 58 41 - Fax. +34 91 883 63 21 International: Tel. +34 91 877 05 10 - Fax. +34 91 877 11 58

www.dirna.com <u>España</u>: ventas@dirna.bergstrominc.com <u>International</u>: sales@dirna.bergstrominc.com